



# ZEBRA CS3000 SERIES

## 1-D LASER SCANNING DEVICE

### ENABLE ANYWHERE ANYTIME COST-EFFECTIVE MOBILE 1-D LASER SCANNING

The innovative Zebra CS3000 Series enables enterprises to easily implement 1-D laser scanning where either mobility or the cost and size of a traditional scanning device is an inhibitor. The tiny device is affordably priced and fits in a pocket or on a lanyard. The CS3000 can be utilized in standalone mode for the batch scanning of bar codes, while the CS3070 offers batch mode as well as real-time bar code data transmission to a host application via a wireless Bluetooth® connection to smartphones, laptops and more. Managing the data in batch mode is easy. Once connected to a host, the batch data can be configured for automatic transfer to an application. Since captured scans are placed in a user-definable standard ASCII file type, the information can be easily utilized to populate order forms, spreadsheets and inventory lists. The result is a new level of affordability for 1-D scanning and the ability to streamline, error proof and simplify more business processes.

### ZEBRA SIGNATURE ERGONOMICS ENSURE USER COMFORT AND EASE OF USE

The easy to use CS3000 Series requires virtually no training to operate. The highly intuitive simple 2-button interface makes scanning easy. In addition, grooves that guide hand and fingers into the most comfortable scanning position combine with soft rubber trigger buttons to bring comfort to the most scan intensive tasks.

### ENTERPRISE CLASS CAPACITY, RELIABILITY AND TOTAL COST OF OWNERSHIP (TCO)

The large memory capacity allows workers to capture over a million bar codes, providing ample support for the largest batch operations. The non-volatile memory ensures that batch data is retained. Built-in business durability provides a low TCO. A 4 ft./1.2 m drop specification and the ability to survive 500 1.64 ft./0.5 m consecutive tumbles combine to ensure dependable operation. And a 24-hour batch/12-hour Bluetooth mode battery cycle time insures well over single shift scanning performance on a charge.

## FEATURES

### Flexible mobile 1-D laser scanner

A mobile bar code scanner with two modes of operation: batch for uploading data to a host at a later time or real-time capture and transmission to a host application via a wireless Bluetooth connection to smartphones, PDAs and laptops

### Long battery life

A 24-hour batch/12-hour Bluetooth mode battery life insures well over single shift scanning performance on a charge

### Simple two button design

Easy to hold and use ' almost no training required

### Small and lightweight

Fits in a pocket or on a neck lanyard and weighs only 2.45 oz./70 gm

## **BEST-IN-CLASS HIGH PERFORMANCE SCANNING**

The integrated SE955 scan engine delivers Zebra's world-renowned scanning quality and reliability. The wide working range provides extraordinary application flexibility, allowing users to capture bar codes from near contact to as far as 45 in./114.3 cm away, in virtually any lighting condition. Aggressive performance enables the capture of even damaged and poor quality bar codes. And a time stamp can be automatically appended to each batch scan, providing additional business intelligence.

## **AUTOMATE YOUR WORKFLOW WITH TWO FLEXIBLE OPERATIONAL MODES ' BATCH AND REAL TIME**

In batch mode, this pocket friendly device allows guards and custodial staff to scan bar codes on entry doors and other locations, and upload the time and date stamped data at the end of a shift to document the accurate completion of activities. Outside the enterprise, manufacturers and distributors can provide customers with a CS3000 to scan inventory as it is used, effectively automating the ordering process at the point of consumption.

In real-time mode, the Bluetooth enabled CS3070 can be paired with virtually any existing smartphone, allowing route drivers to easily scan the items in a delivery or on the store shelves to help automate and error proof the delivery and ordering process.

For more information on how you can put the CS3000 Series to work in your organization, please visit us on the web at [www.zebra.com/cs3000](http://www.zebra.com/cs3000) or access our global contact directory at [www.zebra.com/contact](http://www.zebra.com/contact)

## **Easy to integrate with a host device**

Batch USB connectivity or wireless Bluetooth enables compatibility with virtually any host device

## **512 MB non-volatile memory**

Provides the capacity to store over a million scans and ensures the data is retained ' ideal for virtually any batch operation

## **Superior scanning performance**

Easy and intuitive to use ' just point, click and scan; enables easy capture of even dirty, damaged and poor quality bar codes

## **Enterprise durability: 4 ft./1.2 m drop specification; 250 tumbles (500 drops) @ 1.64 ft./0.5 m**

Ensures reliable operation despite the inevitable drops and bumps in real world use

## **APPLICATIONS**

### **Supply Chain**

Proof of Delivery (PoD);  
Customer Managed  
Inventory (CMI)

### **Facilities Management**

Inspections; Asset Tracking

### **Field Sales**

Merchandising; Account  
Management; Delivery

### **Retail**

Inventory; Gift Registry

## SPECIFICATIONS CHART

PHYSICAL CHARACTERISTICS		USER ENVIRONMENT	
<b>Dimensions</b>	3.41 in. L x 1.95 in. W x .87 in. H 8.65 cm L x 4.95 cm W x 2.2 cm H	<b>Drop Specification</b>	4 ft./1.21 m drop to tiled linoleum over concrete, 6 drops per 6 sides, across the operating temperature range
<b>Weight</b>	With batteries: 2.45 oz./70 gm	<b>Tumble Specification</b>	250 cycles @ 1.64 ft./0.5 m (500 drops)
<b>Scan Engine</b>	SE955 laser, single line	<b>Operating Temperature</b>	32° to 104° F /0° to 40° C
<b>Memory</b>	512MB Flash	<b>Storage Temperature</b>	-40° to 158° F /-40° to 70°C
<b>Memory Capacity</b>	Over 1 million barcodes (UPC with time date stamp)	<b>Humidity</b>	10 to 95% noncondensing
<b>LEDs</b>	Scan LED (Green, Red, and Amber) and Bluetooth® LED (Blue)	<b>Ambient Lighting Tolerance</b>	Tolerant to typical artificial indoor and natural outdoor (direct sunlight) lighting conditions. Fluorescent, Incandescent, Mercury Vapor, Sodium Vapor, LED <sup>1</sup> : 450 Ft Candles (4,844 Lux) Sunlight: 8000 Ft Candles (86,111 Lux)
<b>Buttons</b>	Scan, remove scan (batch mode only), enable Bluetooth (RF scanners only)		
OPERATING MODES			
<b>Batch</b>	Scans recorded with optional time/date stamp		
<b>Open Bluetooth</b>	Real time wireless data transmission		
BATTERY		REGULATORY	
<b>Battery</b>	780 mAh Lithium ion	<b>Laser Safety</b>	EN 60825-1, IEC 60825-1, 21CFR1040.10
<b>Charge Time</b>	3 hours	<b>EMC</b>	CS3000: FCC Part 15 Class B, ICES 003 Class B, EN 55022, EN 55024 CS3070: FCC Part 15 Class B, ICES 003 Class B, EN 55022, EN 55024, EN 301 489-1, EN 301 489-17
<b>Battery Life</b>	Batch - 24 hours use or 8,500 scans (6 scans per minute on full charge) Standby - 3 months Bluetooth - 12 hours use or 4,250 scans (6 scans per minute on full charge)	<b>Radio</b>	CS3070: EN 300 328
<b>Power Consumption</b>	5V, 500mA max while charging	<b>Electrical Safety</b>	UL 60950-1, C22.2 No. 60950-1, EN 60950-1, IEC 60950-1
		<b>Environmental</b>	RoHS Directive 2002/95/EEC
PERFORMANCE CHARACTERISTICS		WARRANTY	
<b>Decode Capability</b>	1-D symbologies	Warranted against defects in workmanship and materials for a period of twelve (12) months	
<b>Interfaces Supported</b>	USB (Mini jack): CS3000 and CS3070 Bluetooth: CS3070	DECODE RANGE	
<b>Real Time Clock</b>	A date/time stamp can be recorded with each bar code scanned (Batch mode)	<b>4 mil:</b>	0.90 ' 4.90 in. / 2.3 ' 12.4 cm
		<b>5 mil:</b>	1.20 ' 7.40 in. / 3.0 ' 18.8 cm
		<b>7.5 mil:</b>	1.60 ' 12.40 in. / 4.1 - 31.5

	operation only)		cm
<b>Batch Communication</b>	USB 2.0	<b>10 mil:</b>	1.60 ' 17.40 in. / 4.1 ' 44.2 cm
		<b>100% UPC:</b>	1.60 ' 23.40 in. / 4.1 ' 59.4 cm
<b>BLUETOOTH</b>			
<b>Bluetooth Radio</b>	Bluetooth, Class 2, Version 2.1 + Enhanced Data Rate (EDR)	<b>15 mil:</b>	1.60 ' 24.40 in. / 4.1 ' 62.0 cm
		<b>20 mil:</b>	1.90 ' 25.40 in. / 4.8 ' 64.5 cm
<b>Bluetooth Range</b>	30 ft./10 m		
<b>Bluetooth Profiles</b>	HID keyboard wedge and Serial Port Profile (SPP)	<b>40 mil:</b>	*- 27.40 in. / *- 69.6 cm
		<b>55 mil:</b>	*- 31.40 in. / *- 79.8 cm

\*Minimum distance determined by symbol length and scan angle

---

### SERVICES

Service from the Start Advance Exchange Support

---

1 - LED lighting with high AC ripple content can impact scanning performance



Part number: SS-CS3000-A. Printed in USA 04/15.©2015 ZIH Corp. ZEBRA, the Zebra head graphic and Zebra Technologies logo are trademarks of ZIH Corp, registered in many jurisdictions worldwide. All rights reserved. All other trademarks are the property of their respective owners.