

DP-88

88 Key Desktop NEMA 4X Keyboard



IKEY Industrial Peripherals
2621 Ridgepoint Dr., Suite 235
Austin, TX 78754
800.866.6506 Telephone
512.837.0207 Fax

INDUSTRIAL RATINGS

NEMA 4, 4X
UL-1950
CE
FCC Class 15, Part B

KEY SWITCH

MATERIAL: Industrial silicone rubber
LIFE: Greater than 10 million cycles
TRAVEL: 0.055" (1.4mm)
ACTUATION FORCE: 5 oz (130g)
FEEDBACK: Tactile with mechanical snap

POWER: 5V@10ma (from CPU port)

TEMPERATURE RANGE

-40F to +194F (-40C to +90C)

HUMIDITY: 100%

SHOCK: 3x11 ms pulses of 50g on each of 3 axes

VIBRATION

POWER SPECTRAL DENSITY: 0.04g/Hz
FREQUENCY RANGE: 20Hz - 2kHz
DURATION OF TEST PER AXIS: 3 hours

FLAMMABILITY

PRINTED CIRCUIT BOARD: 94 VO
SILICONE OVERLAY: 94 HB
INTERFACE CABLE: 94 VO

FEATURES

12 Function Keys
ABS-Polycarbonate Plastic Case
8-32 Mounting Nuts

DIMENSIONS: (W-H-D) 11.4" x 6.3" x 1.86"
289.7mm x 160.0mm x 47.2mm

CABLE LENGTH: 4 ft coiled (1.2m)

COMPATIBILITY: USB, PS/2

WARRANTY: 1 Year Limited Warranty

